

SCOUTCAM'S STARTER KITS - 1.8 mm AND 2.1 mm FOR MEDICAL AND INDUSTRIAL APPLICATIONS

Unleash your medical, industrial and device potential. **ScoutCam Starter Kits** contains the needs to get you going with its high-end, innovative, micro-visualization features. All Starter Kits include semi flexible camera probe, video processing unit, controls and operation instructions.

Key Features	
Camera outer diameter	Φ1.8 mm / Φ2.1 mm
Camera head length	<6.0 mm
Resolution	160 Kpx
Field of view	Default - 120°
Depth of field	5-50 mm
Frame rate	30 fps
Illumination	Fiber-Optics/LED
Camera cable length	Default - 1 meter

PRODUCT REQUEST FORM ▶

I am requesting the following:

ScoutCam Starter Kit (select a camera)	<input checked="" type="checkbox"/>
SCSKCAM18F-SK 400x400px, Φ1.8 mm, FO illumination camera	<input type="checkbox"/>
SCSKCAM21L-SK400x400px, Φ2.1mm, LED illumination camera	<input type="checkbox"/>
SCSKV400CM-SK, VPU400 with composite video and USB power	<input type="checkbox"/>



Thank you for reviewing this information.
info@scoutcam.com | www.scoutcam.com